

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 0103-100	1.5 ... 30 MHz	100 / 120	50 / 52 $\pm$ 2	20 / 20	450	2 HU, 430 mm	14
BLWA 0103-150	1.5 ... 30 MHz	150 / 180	51.8 / 54 $\pm$ 2	20 / 20	500	2 HU, 430 mm	15
BLWA 0103-250	1.5 ... 30 MHz	250 / 300	54 / 56 $\pm$ 2	20 / 18	800	3 HU, 630 mm	18
BLWA 0103-500	1.5 ... 30 MHz	500 / 600	57 / 59 $\pm$ 2	20 / 12	1500	3 HU, 630 mm	28
BLWA 0103-800	1.5 ... 30 MHz	800 / 900	59 / 61 $\pm$ 2	20 / 12	3000	4 HU, 630 mm	38
BLWA 0103-1000	1.5 ... 30 MHz	1000 / 1200	60 / 62 $\pm$ 2	20 / 12	4500	4 HU, 630 mm	43
BLWA 0103-1500	1.5 ... 30 MHz	1500 / 2000	61.8 / 64 $\pm$ 2	20 / 12	5000	5 HU, 630 mm	62
BLWA 0103-2000	1.5 ... 30 MHz	2000 / 2500	63 / 65 $\pm$ 2	20 / 12	7000	7 HU, 630 mm	70
BLWA 0103-3000	1.5 ... 30 MHz	3000 / 4000	64.8 / 67 $\pm$ 2	20 / 12	9000	8 HU, 630 mm	75
BLWA 0103-5000	1.5 ... 30 MHz	5000 / 6000	67 / 69 $\pm$ 2	20 / 12	18000	21 HU, 800 mm	220
BLWA 0103-10000	1.5 ... 30 MHz	10000 / 12000	70 / 72 $\pm$ 2	20 / 12	35000	37 HU, 800 mm	450
BLWA 0103-20000	1.5 ... 30 MHz	20000 / 22000	73 / 75 $\pm$ 2	20 / 12	70000	2x 37 HU, 800 mm	950
BLWA 0103-40000	1.5 ... 30 MHz	40000 / 42000	76 / 78 $\pm$ 2	20 / 12	140000	4x 37 HU, 800 mm	1950

For individual data sheets, please click on the above model name

1 HU = 44.45 mm