

STANDARD MODELS

Model	Frequency Range	Output Power P _N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 0825-250/100/35D	80 ... 2500 MHz				1000	4 HU, 630 mm	38
	80 ... 400 MHz	250 / 300	54 / 56 ±2	20 / 15			
	400 ... 1000 MHz	100 / 150	50 / 52 ±2	20 / 20			
	1000 ... 2500 MHz	35 / 40	45.4 / 48 ±2	20 / 20			
BLWA 0825-250/100/70D	80 ... 2500 MHz				1000	4 HU, 630 mm	54
	80 ... 400 MHz	250 / 300	54 / 56 ±2	20 / 15			
	400 ... 1000 MHz	100 / 150	50 / 52 ±2	20 / 20			
	1000 ... 2500 MHz	70 / 80	48.5 / 51 ±2	20 / 20			
BLWA 0825-250/150D	80 ... 2500 MHz				1250	4 HU, 630 mm	39
	80 ... 500 MHz	250 / 300	54 / 56 ±2	20 / 15			
	500 ... 2500 MHz	150 / 180	51.8 / 54 ±2	15 / 20			
For individual data sheets, please click on the above model name							1 HU = 44.45 mm