

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BLWA 4010-100	400 ... 1000 MHz	100 / 120	50 / 52 $\pm$ 2	20 / 20	500	3 HU, 630 mm	18
BLWA 4010-125	400 ... 1000 MHz	125 / 140	51 / 53 $\pm$ 2	20 / 20	580	3 HU, 630 mm	22
BLWA 4010-200	400 ... 1000 MHz	200 / 230	53 / 55 $\pm$ 2	20 / 20	1150	3 HU, 630 mm	25
BLWA 4010-250	400 ... 1000 MHz	250 / 300	54 / 56 $\pm$ 2	20 / 20	1800	4 HU, 630 mm	35
BLWA 4010-350	400 ... 1000 MHz	350 / 400	55.4 / 58 $\pm$ 2	20 / 20	2200	4 HU, 630 mm	35
BLWA 4010-500	400 ... 1000 MHz	500 / 600	57 / 59 $\pm$ 2	20 / 20	3200	5 HU, 630 mm	50
BLWA 4010-700	400 ... 1000 MHz	700 / 750	58.5 / 61 $\pm$ 2	20 / 20	4000	8 HU, 630 mm	82
BLWA 4010-1000	400 ... 1000 MHz	1000 / 1150	60 / 62 $\pm$ 2	20 / 20	4500	8 HU, 630 mm	85
BLWA 4010-1250	400 ... 1000 MHz	1250 / 1300	61 / 63 $\pm$ 2	20 / 20	6000	18 HU, 800 mm	150
BLWA 4010-1500	400 ... 1000 MHz	1500 / 1700	61.8 / 64 $\pm$ 2	20 / 20	7500	18 HU, 800 mm	150
BLWA 4010-2000	400 ... 1000 MHz	2000 / 2200	63 / 65 $\pm$ 2	20 / 20	15000	24 HU, 800 mm	280
BLWA 4010-3000	400 ... 1000 MHz	3000 / 3300	64.8 / 67 $\pm$ 2	20 / 20	18000	24 HU, 800 mm	280
BLWA 4010-4000	400 ... 1000 MHz	4000 / 4500	66 / 68 $\pm$ 2	20 / 20	28000	37 HU, 800 mm	450
BLWA 4010-5000	400 ... 1000 MHz	5000 / 5500	67 / 69 $\pm$ 2	20 / 20	34000	37 HU, 800 mm	450

For individual data sheets, please click on the above model name

1 HU = 44.45 mm