

STANDARD MODELS

Model	Frequency Range	Output Power P_N min / typ W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power VA	Dimensions (H, D) 19"-System	Weight kg
BSA 0040-75	4 kHz ... 400 MHz				700	2 HU, 430 mm	14
	4 ... 9 kHz	30 / 40	44.8 / 47 ±2	20 / 20			
	9 kHz ... 400 MHz	75 / 100	48.8 / 51 ±2	20 / 20			
BSA 0040-150	4 kHz ... 400 MHz	150 / 180	51.8 / 54 ±2	20 / 20	1250	3 HU, 630 mm	29
BSA 0040-200	4 kHz ... 400 MHz				1300	3 HU, 630 mm	34
	4 ... 9 kHz	150 / 160	51.8 / 54 ±2	20 / 15			
	9 kHz ... 400 MHz	200 / 230	53 / 55 ±2	20 / 20			
BSA 0040-250	4 kHz ... 400 MHz				2500	4 HU, 630 mm	38
	4 ... 9 kHz	60 / 75	47.8 / 51 ±3	20 / 15			
	9 kHz ... 400 MHz	250 / 270	54 / 56 ±2	20 / 20			

For individual data sheets, please click on the above model name

1 HU = 44.45 mm