

## STANDARD MODELS

| Model         | Frequency Range     | Output Power<br>$P_N$ min / typ<br>W | Gain<br>min / typ<br>dB | Harmonics<br>2nd / 3rd<br>dBc | Line Power<br>VA | Dimensions<br>(H, D)<br>19"-System | Weight<br>kg |
|---------------|---------------------|--------------------------------------|-------------------------|-------------------------------|------------------|------------------------------------|--------------|
| BSA 1025-40   | 100 kHz ... 250 MHz | 40 / 45                              | 46 / 48 $\pm 2$         | 20 / 20                       | 350              | 2 HU, 430 mm                       | 13           |
| BSA 1025-100  | 100 kHz ... 250 MHz | 100 / 110                            | 50 / 52 $\pm 2$         | 20 / 20                       | 510              | 2 HU, 430 mm                       | 14           |
| BSA 1025-150  | 100 kHz ... 250 MHz | 150 / 170                            | 51.8 / 54 $\pm 2$       | 20 / 20                       | 530              | 2 HU, 430 mm                       | 14           |
| BSA 1025-200  | 100 kHz ... 250 MHz | 200 / 240                            | 53 / 55 $\pm 2$         | 20 / 20                       | 800              | 3 HU, 630 mm                       | 21           |
| BSA 1025-250  | 100 kHz ... 250 MHz | 250 / 280                            | 54 / 56 $\pm 2$         | 20 / 20                       | 800              | 3 HU, 630 mm                       | 21           |
| BSA 1025-400  | 100 kHz ... 250 MHz | 400 / 450                            | 56 / 58 $\pm 2$         | 20 / 18                       | 1850             | 4 HU, 630 mm                       | 37           |
| BSA 1025-500  | 100 kHz ... 250 MHz | 500 / 600                            | 57 / 59 $\pm 2$         | 20 / 18                       | 2300             | 4 HU, 630 mm                       | 52           |
| BSA 1025-1000 | 100 kHz ... 250 MHz | 1000 / 1100                          | 60 / 62 $\pm 2$         | 20 / 20                       | 3100             | 5 HU, 630 mm                       | 65           |
| BSA 1025-1250 | 100 kHz ... 250 MHz | 1250 / 1350                          | 61 / 63 $\pm 2$         | 20 / 20                       | 6500             | 10 HU, 630 mm                      | 110          |
| BSA 1025-2500 | 100 kHz ... 250 MHz | 2500 / 2700                          | 64 / 66 $\pm 2$         | 20 / 20                       | 13000            | 24 HU, 800 mm                      | 265          |

For individual data sheets, please click on the above model name

1 HU = 44.45 mm